

Battery-powered starter suitable for 12-24V starting of cars, vans, boats, agricultural vehicles, power sources etc. When connected to the cigar-lighter outlet it maintains the voltage on all circuits during battery changes and is also a 12V power source for use in emergencies. Fit with a safety switch for starting, it does not damage the electronics of the vehicle and allows for a large number of starting operations before being recharged. PRO START 2824 can be recharged using the special power supply, connected to the mains network, or using the cigar-lighter outlet of the vehicle (for the safeguard of the battery, charge for 12 hours before use, charge again after each use and every 3 months in any case). Characteristics: safety switch \* overload protection \* polarity reversal protection acoustic/luminous alarm \* high efficiency led lamp \* battery charge status led \* battery charging status led \* 2 x 12V jack sockets \* cable-holder pocket. Complete with: 230V AC 12V DC power adaptor, positive-negative cables with clamps, high efficiency lamp, double jack cable.



AUTOMOTIVE

PROFESSIONAL



Norms:	LVD: EN 61558-1	EMC: EN 55014-1,2;	EMC: EN 61000-3-2,3						
CODE	V <sub>ph</sub> V	START V	A <sub>h</sub> Ah	A <sub>OUT</sub> A	A <sub>START MAX</sub> A	W <sub>H</sub> cm(L,W,H)	kg	BAR CODE	pz/pallet
829517	230 1 ph	12 24	44 22	800	2500	20,5 33,5 36	15,1	8004897837 56 7	26
pz/pallet - B									
39									