

MMA inverter, electrode welding machine in direct current (DC). Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc. Characteristics: compact and light * high welding current stability in spite of mains voltage fluctuations * arc force, hot start and anti-stick devices * thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections. Complete with TIGER helmet and MMA welding accessories.

NEW

PROMOTION PACKAGE

INVERTER
**WITH MASK
CARRY CASE
ACCESSORIES**

CONSUMER



20°C	ELECTRODES IN 10 MIN			20" STOP
Ø (I)	1,6mm (40A)	2,0mm (55A)	2,5mm (80A)	3,2mm (125A)
10 MIN	10,3	8,3	7,3	4,7
%USE ^(*) 20°C	100%	100%	93%	60%


**COMPLIANCE WITH NEW
CE MARKING**

**SUPPLY WITH
MOTOGENERATORS
(VIN +/-15%)**

**MOTOGENERATOR
POWER - SOURCE**
**ARC FORCE, HOT
START, ANTI-STICK
DEVICES**

**ARC FORCE
HOT START
ANTI STICK**
**MANUAL CLOSING
PROTECTIVE FILTER**

**STEEL, STAINLESS
STEEL, CAST IRON**


Norms:		LVD: EN 60974-1		LVD: EN 50445		EMC: EN 60974-10			
CODE	V _{ph} V50/60Hz	A _{MIN} A	%USE _{20°C} %	A _{MAX} 40°C A EN60974-1	V _o V	A _{MAX} A	P _{MAX} kW	P _{GEN} kW	A
815862	230 1 ph	10 130 DC	60% 125A	125 7% DC	72 DC	27	3,5	5	16
η	cosφ	Ø _{MIN} MAX mm	IP	W _H cm(L,W,H)	kg	BAR CODE	pz/pallet		
82	0,6	1,6 3,2	IP21	30 12,5 22,5	4,21	8004897791 51 7	24		

(*)%USE: DATUM CREATED BY TELWIN, NOT INCLUDED IN THE EN 60974-1.

Telwin does not accept any responsibility for possible inaccuracies contained in this document